(12) UK Patent Application (19) GB (11) 2 186 884(13) A

(43) Application published 26 Aug 1987

- (21) Application No 8704038
- (22) Date of filing 20 Feb 1987
- (30) Priority data (31) 8604164 8616137
- (32) 20 Feb 1986 2 Jul 1986
- (33) GB

(71) Applicants

Albright & Wilson Limited

(Incorporated in United Kingdom)

Albright & Wilson House, Hagley Road West, Oldbury, Warley, West Midlands.

Novo Industri A/S

(Incorporated in Denmark)

Novo Alle, DK-2880 Bagsvaerd, Denmark

(72) Inventors **Edward Tunstall Messenger** Arne Ditley Foo **Anthony Martin** Per Falholt

(51) INT CL4 C11D 3/386

(52) Domestic classification (Edition I): C5D 6A4A 6A5A 6A5B 6A5C 6A5D1 6A5D2 6A5E 6A6 6A8B 6A9 6B10A 6B11A 6B11C 6B12B1 6B12C 6B12F1 6B12F2 6B12G1 6B12G2A 6B12L 6B12N1 6B12N2 6B13 6B14 6B1 6B2 6B4 6B7 6B8 6C8

(56) Documents cited

GB 1403173 GB 1386674 GB 1363027 GB 1255284 EP A2 0163352 EP A1 0040091

(58) Field of search

C5D СЗН

B8C

Selected US specifications from IPC sub-classes C11D

(74) Agent and/or Address for Service R. G. M. Savidge,

c/o Albright & Wilson Limited, 1 Knightsbridge Green, London SW1X 7QD

(54) Protected enzyme formulations for use in detergent compositions

(57) A protected enzyme system suitable for storage, prior to use, in a medium such as a liquid detergent which causes degradation of the unprotected enzyme, comprises an enzyme dispersed in a hydrophobic substance which does not dissolve on storage and which is liquid under the conditions of use, or the enzyme may be encapsulated in on or coated with a hydrophobic substance such as petroleum jelly. The enzymes may be those used in detergent compositions.

THIS PACE OLAM (1990)

Protected enzyme systems

	Protected enzyme systems	
5	The present invention relates to protected enzyme systems which are suitable for storage or use in environments which tend to cause degradation of enzymes, such as liquid laundry detergents. Enzymes are commonly employed as stain removing agents in powder detergents, but their incorporation in liquid cleaning preparations including liquid laundry detergents, such as those	5
10	described for example in GB 2123846 and GB 2153380 has hitherto presented serious problems. Those liquid formulations which are most effective for soil removal cause rapid degradation of washing enzymes, often resulting in significant loss of stain removing properties after only a few days of storage. The relatively high alkalinity of the more effective soil removing formulations and the chemical action of most of the builder systems and surfactants present therein are	10
15	particularly antagonistic to detergent enzymes and have largely prevented their use in such detergents, but serious deterioration is observed even in comparatively non-alkaline compositions, which have been specially formulated to permit incorporation of enzymes. Even in powder detergents some degradation of enzymes may be observed, especially if the powder is highly alkaline as in mechanical dishwashing powders, or contains an oxidising bleach such as	15
20	We have now discovered that the deterioration of enzymes in hostile environments such as liquid detergents is substantially reduced when the enzymes are dispersed in a hydrophobic material provided that the latter is insoluble in the particular environment. We have discovered, moreover, that the protected enzyme is available to perform its normal function provided that the hydrophobic material is sufficiently fluid or friable to be disrupted under the conditions of	20
25	use. According to one embodiment, therefore, our invention provides a protected enzyme system for storage prior to use, in an environment which causes progressive degradation of unprotected enzymes, said system consisting essentially of a dispersion of at least one enzyme in a hydro-	25
30	phobic substance which is insoluble in the said environment, and which is sufficiently fluid or friable to be disrupted under the normal conditions of use. According to a preferred aspect our invention provides a protected enzyme system for use in a liquid cleaning composition said system comprising at least one detergent enzyme dispersed in a hydrophobic substance which is insoluble in the liquid detergent but dispersible therein as	30
35	particles or droplets, and which is sufficiently fluid or friable to be disrupted under cleaning conditions. According to a second embodiment our invention provides a protected enzyme system for use in a liquid cleaning composition consisting essentially of granules comprising at least one deter-	35
40	gent enzyme encapsulated within a hydrophobic substance which is not soluble in the liquid cleaning composition and which is fluid or friable at normal wash temperatures. According to a third embodiment our invention provides a protected enzyme system for use in liquid detergent compositions consisting essentially of a dispersion of a detergent enzyme in a hydrophobic liquid which is insoluble in liquid detergent. According to a fourth embodiment our invention provides a method of protecting an enzyme	40
45	for storage prior to use in an environment which tends to cause progressive degradation of unprotected enzymes, which method comprises dispersing the enzyme in a hydrophobic medium which is insoluble in said environment but dispersible therein as particles or droplets and which is fluid or friable under the normal conditions of use.	45
50	According to a fifth embodiment our invention provides a method of protecting enzymes which comprises dispersing a detergent enzyme in a hydrophobic substance which is insoluble in liquid detergent, and fluid at normal wash temperatures. According to a sixth embodiment our invention provides a liquid cleaning composition having dispersed therein particles or droplets of a protected enzyme system of our invention as	50
55	hereinbefore described. References herein to solubility in a medium refer to both dissolution in an aqueous or other continuous solvent phase of the medium and solubilisation in surfactant micelles or any other discontinuous phase dispersed in the medium.	55
60	The hydrophobic material may be an organo polysiloxane oil, e.g. a poly di(alkyl)siloxane, wherein the alkyl group has preferably from 1 to 4 carbon atoms, especially a poly di(methyl)siloxane. Especially preferred are hydrophobic liquids which have been stabilised by suspending therein hydrophobic solid particles. Examples include the silicone compositions which have been proposed for use as antifoam in liquid detergents which comprise hydrophobic silicone oil and hydrophobic silica e.g. a finely divided silica with a silicone at least partly bonded to the surface	60
65	of the silica particles. For example a hydroxy functional organosiloxane may be condensed with the hydroxy groups of the silica surface. Examples of such compositions include those sold under the Registered Trade Marks "WACKER" Antifoam S132, "BEVALOID" 4237, "UNION	65

65

CARBIDE" Y1206, or DIAMOND SHAMROCK'S "NOPCO" 8315. The silicone antifoam may be diluted with an unmodified silicone oil such as a poly dimethyl siloxane. Furthermore the viscosity of the silicone may be increased by addition of finely divided silica eg, fumed silica such as Degussa's "Aerosii" 200 (RTM). 5 Alternatively the hydrophobic material may be a high molecular weight hydrocarbon, e.g. petroleum bright stock or a so-called petroleum jelly, a high molecular weight alcohol, e.g. more than 28 carbon atoms or a high molecular weight fluocarbon or a hydrophobic phosphate ester such as a mono- and/or di- fatty alkyl phosphate ester or a salt thereof, especially a sodium or calcium salt or a trialkyl or triaryl phosphate. Hydrophobic fluid materials may be further stabil-10 ised by inclusion of hydrophobic solid particles, e.g. those formed by condensing silica with 10 silicone as described above or with a fatty alcohol. According to one embodiment the hydrophobic material may be a solid or waxy material at ambient temperature, which has a softening or preferably melting point below normal wash temperature, e.g. below 60°C, preferably below 50°C more usually 40°C, often below 30°C. Such solid materials provide products which are 15 particularly suitable for use in powder as well as liquid detergents. Typically we prefer that our 15 hydrophobic material has a viscosity greater than 0.05 Pascal seconds at normal storage temperature (e.g. room temperature) preferably greater than 0.2, more preferably greater than 0.5 and most preferably greater than 0.8 Pascal seconds. In particular we prefer that the viscosity should be greater than 1 Pascal second e.g. greater than 2 Pascal seconds, especially greater than 10 20 Pascal seconds. We prefer that the viscosity should be less than 200 Pascal seconds, most 20 preferably less than 100 Pascal seconds, e.g. less than 60 Pascal seconds and especially less than 40 Pascal seconds, at the temperature of use. Fluid materials having a viscosity between 1 and 50 Pascal seconds at ambient temperature are especially suitable. Unless stated to the contrary, all references herein to viscosities are as measured at 24 sec-1 25 25 shear and at 25°C. The enzyme may for example be a detergent enzyme, such as a protease, lipase, amylase, decarboxylase, or cellulase, such as those sold by Novo Industri AS under the Registered Trade Marks "SAVINASE", "TERMAMYL", "ESPERASE" and "ALCALASE", or other enzymes which are active in the removal or amelioration of soil or stains or a mixture of such enzymes. The enzyme may be present in the hydrophobic material in the form of dispersed droplets of a 30 solution of enzyme, e.g. in water or a lower, preferably water miscible, mono-, di- or polyhydric alcohol such as propylene glycol and optionally containing an enzyme stabiliser such as is known in the art. Enzyme stabilisers which may be present include lower alcohols, e.g. glycerol, lower mono- or di-carboxylic acids and their salts, especially formates and oxalates, borates and 35 35 calcium salts. Alternatively the enzyme may be present in the form of suspended particles of an enzymecontaining solid, the solid enzyme being preferably obtained by drying or precipitation from an enzyme solution, optionally containing a stabiliser as aforesaid, e.g. as described in US 3 723 250, particularly at column 12; EP 0 006 638, Example 2a and b GB 1,296,839; U.S. 40 4,435,307; EP 0 130 064 or Belgian Patent 889336. 40 The enzyme may also be present in a water soluble granule or marume. Typically this is the form in which enzymes are sold commercially. Thus a soluble crystalline carbohydrate such as sucrose or a salt such as sodium chloride, sodium carbonate or sodium sulphate may be granulated or marumerised with the enzyme, and, optionally, with enzyme stabilisers, e.g. as 45 described in U.S. 4,106,991 or GB 1,362,365, page 9, and the product dispersed in, or coated 45 with, silicone or a hydrocarbon, such as petroleum jelly. The enzyme may be incorporated in the inert oil by dispersion by simple stirring. Where the hydrophobic material is solid at room temperature it may first be melted before dispersing the enzymes and subsequently cooled to room temperature. Optionally the dispersion may be spray 50 50 cooled to provide a particulate product. The proportion of enzyme in the protected enzyme system may be determined by the desired viscosity of the system, where it is desired to handle or store the latter as a liquid. Higher proportions tend to provide higher viscosities, but are less prone to sedimentation of the dispersed enzyme. However, we do not exclude the use of sedimenting systems provided that 55 the enzymes can be easily redispersed by stirring before the system is added to the detergent 55 composition. Preferably the particle size and proportion of the enzyme are chosen to provide an overall viscosity of the protected system greater than 0.1 Pascal seconds, typically greater than 0.5 Pascal seconds especially greater than 1 Pascal second more preferably greater than 2 Pascal 60 seconds, e.g. greater than 3 Pascal seconds and optionally greater than 10 Pascal seconds, 60 under the conditions of storage and less than 200 Pascal seconds, more preferably less than 100 Pascal seconds, e.g. less than 70 Pascal seconds under the conditions of use. Systems having a viscosity in the range of 2 to 60 Pascal seconds at ambient temperature are generally preferred.

Where enzyme is incorporated in the system as a solution, the solution preferably contains 1

5	to 90% by weight of enzyme concentrate, e.g. 2 to 80%, typically 5 to 60%, and its dispersion in the oil typically contains 1–80, more usually 5–70, preferably 10–60, more preferably 15–50, e.g. 20–40 or 30–50% by weight of enzyme solution, the percentages being expressed by weight of the total protected enzyme system. The suspension of solid enzyme concentrate in the hydrophobic material typically contains 1 to 90, more usually 5 to 80, preferably 20–60, e.g. 30–50 or 20–30% by weight of solid, based on the total weight of suspension. The proportion of enzyme in the protected enzyme system may depend on whether the	5
10	hydrophobic substance is required to perform any useful function in its own right, e.g. as antifoam. Where a low foaming composition is required the enzyme and antifoam may conveniently be in the same relative proportions as those which are required in the final composition. Alternatively a more concentrated suspension of enzyme may be prepared and diluted with more antifoam prior to use, or added to the composition simultaneously with or separately from the additional antifoam.	10
15	Where the hydrophobic material is not required to perform a useful function other than protecting enzyme, the enzyme concentration may be the maximum which is consistent with a manageable product.	15
20	The particle size of the dispersed enzyme in the protected enzyme system can vary within wide limits. Typically the dispersed enzyme may have a particle size in the range 1μ to 2mm, preferably 5μ to 1mm, e.g. 10μ -700 μ . Solid enzyme concentrates tend to be in the lower part of the above range, liquid solutions are normally dispersed with a particle size in the middle of the range, e.g. 100μ -800 μ . Granular enzymes usually have a particle size in the upper part of	20
25	the range, e.g. 300μ -1mm. The protected enzyme system is generally readily dispersed in the liquid detergent by simple stirring. The system may be dispersed as particles or droplets of from 2μ to 2.5mm diameter, more usually 5μ -500 μ , preferably 10μ -100 μ , where a dispersed solution or concentrate of enzyme is used as the protected system. Where the enzyme is present as a granulate, the preferred particle size of the system in the liquid detergent is 500μ to 1mm.	25
30	Dispersants and emulsifiers may be used as required but are not usually preferred. Preferably the composition is added to a liquid detergent which comprises an aqueous phase, surfactant, sufficient electrolyte dissolved in the aqueous phase to form with the surfactant, a structure capable of supporting suspended particles, and a protected enzyme system of our invention, suspended in the detergent composition.	30
35	Preferably the composition contains an effective amount of a detergent builder. Suitable builders include condensed phosphates, especially sodium tripolyphosphate or, less preferably, builders include condensed phosphates, especially sodium reproprietables and improvements are improved and improvements and impr	35
40	include potassium or lithium analogues of the above sodium salts.	40
45	dium nitrilotriacetate with sodium citrate. Preferably the builder is at least partly present as solid particles suspended in the composition. Particularly preferred are liquid detergent compositions according to the aforesaid	45
50	polar surfactant which may typically be present in concentrations of from 2 to 35% by weight of the composition preferably 5 to 30%, more usually 7 to 25%, e.g. 10 to 20%.	50
55	Usually the composition contains an alkyl benzene sulphonate together with one or more other surfactants such as an alkyl polyoxyalkylene sulphate and/or a non-ionic surfactant. The latter may typically be an alkanolamide or a polyoxyalkylated alcohol. Other anionic surfactants include alkyl sulphate, alkane sulphonates, olefin sulphonate, fatty ester, sulphonates, soaps, alkyl sulphosuccinates, alkyl sulphosuccinamates, taurides isethionates	55
60	and polyoxyalkylene derivates of the aforesaid categories of anionic surfactant. In every case the surfactant for use herein has an alkyl group with an average of from 8 to 22 preferably 10 to 20, e.g. 12 to 18 carbon atoms. Alkyl groups are preferably primary and straight chain, however we do not exclude branched chain or secondary alkyl groups. In the case of alcohol based non-ionics the branched chain are sometimes preferred.	60
65	The surfactant may be wholly or predominantly non ionic, e.g. a polyoxyalkylated alcohol alone or in admixture with a polyoxyalkylene glycol. Other non-ionic surfactants which may be used include polyoxyalkylated derivatives of carboxylic acids, glycerol, sorbitan, alkylphenols, alkylo-	65

10

15

20

25

30

35

40

45

50

55

60

À.

lamides	or	amine	oxid	tes.
---------	----	-------	------	------

All references herein to polyoxyalkylene groups are preferably to polyoxyethylene groups, or less preferably to polyoxypropylene or mixed oxyethylene oxypropylene copolymeric or block copolymeric groups or to such groups with one or more glyceryl groups. Preferably the polyoxy-salkylene groups have from 1 to 30, more usually 2 to 20, e.g. 5 to 15, alkyleneoxy units.

Cationic surfactants for use according to our invention include quaternised alkyl amines, amido amines and imidazolines. Amphoteric surfactants include betaines and sulphobetaines.

In general any surfactant referred to in GB 1,123,846, or in "Surface Active Agents and Detergents" by Schwartz, Perry and Berch, may be used.

Preferably the pH of the liquid detergent composition is alkaline, e.g. about 7.5, especially 7.5 to 12 typically 8 to 11, e.g. 9 to 10.5.

Preferably the liquid detergent composition contains dissolved electrolyte. This may comprise a dissolved portion of the builder and/or any other salt, inorganic or organic, which is not itself a surfactant and which salts out the surfactants present from solution (including micellar solution). Examples include sodium chloride, sodium promide, sodium include, sodium bo-

15 Examples include sodium chloride, sodium nitrate, sodium bromide, sodium iodide, sodium borate, sodium formate, or sodium acetate, or corresponding potassium salts. Preferably, however, the electrolyte is a salt which is required to perform a useful function in the wash liquor.

The electrolyte may comprise sodium sulphate in minor concentrations, but electrolyte mixtures containing concentrations of sodium sulphate of about 3% or over based on the total weight of the detergent composition, are preferably not used because they give rise to undesirable crystallisation on standing.

The detergent composition may contain any of the usual minor ingredients such as soil suspending agents (e.g. carboxymethyl cellulose), optical brightening agent, perfume, colouring and, optionally, a bleach.

Particularly preferred liquid detergents are those containing long chain, e.g. C₁₀₋₁₄ linear alkyl benzene sulphonates in an amount of 5–12%, long chain alkyl ether sulphates, e.g. with 1–5 ethyleneoxy units in amount of 0–3%, fatty acid alkanolamides, e.g. diethanolamides in amount of 1–5%, mixtures of mono and di long chain alkyl phosphates in amount of 0–3%, e.g. 0.1–1%, sodium tripolyphosphate (preferably pre-hydrated with from 0.5 to 5% by weight of water) in an amount of 14–30%, e.g. 14–18% or 20–30% and optionally sodium carbonate in an amount of up to 10%, e.g. 5–10%, with the total of sodium tripolyphosphate and carbonate of 20–30%, antiredeposition agents such as sodium carboxymethyl cellulose in amount of 0.05–0.5%, optical brightening agent in amount of 0.05–0.5%, chelating agents, e.g. amino phosphonates such as methylene phosphonates of di and polyamines especially sodium ethylene

35 diamine tetra[methylene phosphonate] or diethylene triamine hexa[methylene phosphonate] optionally present in amount of 0.1–1%, together with conventional additives such as perfume, the remainder being water, the percentages being by weight of the total liquid detergent. The liquid detergent may have a pH of 6 to 13, preferably 7 to 12, more usually 8 to 11, e.g. 9 to 10.5.

The compositions of the invention may typically contain 0.01 to 10%, e.g. 0.05-0.5% by 40 weight of the protected enzyme system.

Our protected enzyme systems are useful as additives to powder cleaning compositions. For instance enzyme dispersed in silicone antifoam or viscous hydrocarbon may be incorporated into a powder laundry detergent. Conventionally such powders may contain surfactant (usually in total amounts of from 5 to 30% by wt.), builder, a solid filler and optionally a bleach. Usually the surfactant comprises a sodium alkyl (preferably C₁₂₋₁₄ linear) benzene sulphonate in amounts of from 2 to 20%, preferably 5 to 15%, by weight of the total composition and optionally a sodium alkyl (e.g. C₁₂₋₁₈) polyoxyethylene (e.g. 2 to 10% mole) sulphate and/or a non-ionic surfactant such as an alkanolamide, e.g. coconut, mono- or di- ethanolamide and/or a polye-

thoxylated fatty alcohol.

The builder is typically sodium tripolyphosphate although zeolites, sodium carbonate, sodium silicates, sodium citrate, sodium nitrilotriacetate and mixtures thereof may be present as well as or in place of sodium tripolyphosphate. The total amount of builder is usually between 10 and

40% by weight of the total powder, e.g. 20 to 30%.
The filler is typically sodium sulphate which may typically be present in a proportion of from 0
to 60% usually 20 to 50% of the total composition in order to ensure a free flowing powder.
The bleach is normally a peroxy compound especially a perborate or percarbonate.

The powder also usually contains the usual minor ingredients such as soil suspending agent (typically sodium carboxymethyl cellulose) optical brightening agent and perfume and optionally colouring.

Protected enzyme systems according to our invention may be added to machine dishwashing powders, scouring creams and other hard surface cleaners, carpet shampoos, degreasing compositions, oven cleaners, dishwashing liquids, soap powders, laundry pre soak compositions and other cleaning preparations.

Dishwashing powders according to our invention may typically comprise a substantial propor-65 tion, e.g. 20 to 60%, preferably 30 to 50%, of an alkali such as a sodium carbonate and a

65

				
	minor proportion, e.g. 1 to 5%, of surfactant preferably a non-ionic surfactant such as an alkoxylated alcohol, together, optionally but preferably, with a builder such as sodium tripo phosphate in proportions of up to about 45% by weight of the composition, e.g. 20 to 35 alkaline silicate such as sodium metasilicate and an alkaline buffer such as borax. The com 5 sition may optionally contain a bleach such as chlorinated trisodium phosphate and from 0	o %, an po-		
5	2% by weight of the protected enzyme system. Liquid dishwashing compositions of our invention typically comprise highly soluble builde such as notes in a pyrophosphate, and/or notes in a total concentration of 10	rs to		
10	30% by weight, surfactants, preferably non-ionic in concentrations of 0.2 to 5% by weight by hydrotropes such as sodium xylene sulphonate, sodium toluene sulphonate or sodium benzallahopate in concentrations of 1 to 10% by weight.	t and zene 10		
	Hard surface cleaners of our invention may typically comprise 1 to 10%, surfactant, typically comprise 1 to 10% soluble builder as potassium pyrophosphate. Hard surface cleaners may also optionally comprise abrasives	Such		
15	as silica, or calcium carbonate as arragonite or calcite suspended in a structural liquid. Carpet shampoos according to our invention may according to our invention comprise re high concentrations, e.g. 5 to 20% by weight, of high foaming surfactants such as mixture anionic surfactants (e.g. alkyl sulphates) with foaming agents (e.g. alkanolamides).	elatively es of		
20	Oven cleaners according to our invention may be of the caustic type comprising, e.g. 4 12% of alkalis such as sodium hydroxide, and typically a high foaming anionic surfactant s a sodium alkyl ether sulphate, or else of the solvent based type containing e.g. 10 to 30% water miscible organic solvent such as a lower mon- di- or polyhydric alcohol or other alcohol. Propylene glycol, and typically a non ionic surfactant, together preferably with a builded.	och as 20 6 of a ohol,		
25	as sodium tripolyphosphate.	25		
30	Normal wash conditions for laundry detergents involve temperatures of from 50°C to 60°C and a wash liquor containing about 2 to 15 gm per litre of detergent composition under vigorous agrication. Some detergents however, are formulated and recommended for use at cool or 3			
	intermediate wash temperatures (20 to 30 or 30 to 40°C respectively), either for sensitive fabrics or energy saving. The invention is illustrated by the following Examples.			
35	Example 1 A protease solution, sold under the Registered Trade Mark "Esperase" 8 OL. was disperate a mixture of equal parts by weight of an antifoam silicone oil having a viscosity of 22.57	Pascai		
40	with solid fumed silica, and is sold under the Registered Trade Mark "Wacker" Antifoam S132, and a neutral polysiloxane oil, sold under the Registered Trade Mark "Wacker" AK50. The silicone mixture had a viscosity of 3.4 Pascal seconds. The dispersion produced contained 38% by weight of the enzyme solution, based on the total weight of dispersion and had a viscosity			
45	of 11.9 Pascal seconds at 24 sec 1 and 25°C. The dispersion was incorporated by thorough stirring into a liquid built detergent to give following formulation:	the 45		
	wt.%			
	Sodium linear C ₁₂ alkyl benzene sulphonate 9.3 Sodium linear C ₁₂₋₁₈ alkyl ether sulphate containing			
50	0 an average of 3 ethyleneoxy units per molecule 1.85	. 50		
	Coconut diethanolamide 1.85 Sodium tripolyphosphate 16.7			
	Sodium carbonate 6.7			
55	Sodium carboxymethyl cellulose 0.9 5 Optical brightening agent 0.1	55		
50	Enzyme dispersion 3			
60	This formulation was compared with the same formulation without enzyme as Control for removal from a test sample of cotton stained with blood, milk and carbon (EMPA 116) at concentration of 5gl ⁻¹ in wash water containing 200ppm calcium carbonate at a wash ter	ta 60		
	ture of 60°C for 30 minutes. The following percentages stain removal were observed:			

å.

60

60 Examples 6 to 13

	Control	36%		
	Freshly prepared formulation	57%		
	Formulation after standing 22 days a	t 30°C 52%		_
5				5
	Examples 2 and 3 A 25% by weight suspension was	nrangrad by stirr	na solid "ESPERASE" prot	ease concen-
	trate (prepared as described in U.S.	Patent No. 3.723.	250 at col. 12) into a silice	one oil with a
	viscosity of 1.83 Pascal seconds, wh			
10	"NOPCO 8315" silicone defoamer.			10
	The suspension had a viscosity of		nds and was incorporated	into built liquid
	detergents to give the following form	iulations.		
		Ex.2	Ex.3	
15	Sodium dodecyl benzene sulphonate	6%	7%	15
	Sodium linear C ₁₂₋₁₈ alkyl ether			
	sulphate containing an average of	2%		•
	3 ethyleneoxy units per molecule Coconut diethanolamide	1.5%	3%	
20	Mixture of mono and di C ₁₆₋₁₈ alkyl	1.075		20
	phosphate ester	0.5%	0.5%	
	Sodium tripolyphosphate	24%	24%	
	Sodium carboxymethyl cellulose	0.1% 1.25%	0.1% 1.25%	
25	Enzyme suspension in silicone oil Optical brightening agent	0.2%	0.2%	25
20	Diethylene triamine penta(methylene	5.2.7		
	phosphonate) sodium salt	0.5%	0.5%	. •
	Perfume	0.3%	0.3%	
30	Water	to 100% about 9.0	to 100% about 9.0	30
30	pri	about 0.0	ubout 0.0	55
	The protease activity of the formula	lation of Example	2 was 15.4 kilo Novo prot	eąse units
	(KNPU) per g.			
25	Examples 4 and 5			35
33	In the same manner as in Example	s 2 and 3, a 25%	by weight suspension of	
	ASE" (Reg. Trade Mark) protease so	olid concentrate in	another silicone antifoam of	oil having a
	viscosity of 1.22 Pascal seconds ("E			
40	built liquid as in Examples 2 and 3 to respectively. The suspension had a v			les 4 and 5 40
40	The protease activity of the formula			40
	p.0.0000 uo, or and remain			
	Storage Stability Tests			
AE	The stability of the formulations of determined and compared to that of	Examples 2 and	4 on keeping at 3/°C for the	o weeks were ample 2 with 45
45	the same amount of enzyme but no		reference formulation to Ex	ample 2 with 45
	The residual proteolytic activity of		was determined by the dim	ethylcasein
	(DMC) method described in Novo Pu			
	following table with activity expresse	ed as a percentage	e of the initial activity of the	
50	Residual Activity aft	er time in weeks		50
	Trestadal Activity dit	CI tillo ili WCCKO		
	Formulation 2 4	5		
55	Example 2 80% 70%			55
	Example 4 85% 65%			
	Reference 33% 9%	6 n.a.		

A number of alternative protected enzyme systems were each prepared by stirring 25% of solid enzyme concentrate into the hydrophobe and tested as shown in the following Table:

Example No	Enzyme	Trade Name of Hydrophobe	Chemical Type of Hydrophobe	Viscosity P Sec. of Hydrophobe	Viscosity of system in P. Sec.	
6	"TERMAMYL"	"BEVALOID"* 4237	Silicone oil+ hydrophobic silica	1.22	2.44	
7	"SAVINASE"	**	"	,,	2.74	
8	"ALKALASE"	"	,,	,,	2.13	
9	,,	"WACKER" \$132+ "WACKER" AK50	diluted with silicone oil		9.76	
10	"TERMAMYL"	"	"		10.06	
11	"ESPERASE"	"CATANEX"* 79	Petroluem bright stock	1.62	4.09	
12	"ESPERASE"*	"VASELINE"	Petroleum jelly			
13	"ESPERASE"*	"EMPICOL"* 7062P	mixed mono/di C ₁₆₋₁₈ alkyl acid phosphate			
14	"ESPERASE"	"WACKER"* S132	Silicone oil+ hydrophobic silica	22.7		
Each of accordinactivity	red Trade Mark. Examples 6 to 14 g to Example 3. and stain removal temperature.	Each was found	to exhibit subs	tantially impro	ved retention	of enzyme
Example A dish	15 nwashing powder	has the following	ng formulation:			
(Regis Sodium Chlorina	cohol 12 mole eth tered Trade Mark tripolyphosphate ted trisodium pho	"EMPILAN" KO	CMP 0705/F)	2% 30% 9%		
Example	metasilicate 10 carbonate			2% 8% 0.5% balance		
Example A dist	e <i>16</i> hwashing liquid ha	s the following	formulation:			

in an environment which causes progressive degradation of unprotected enzymes, said system 65 comprising a dispersion of at least one enzyme in a hydrophobic material which is substantially

8

GB 2 186 884A

8

ä,

65

	insoluble in the said environment, and which is sufficiently fluid or friable to be disrupted under the normal conditions of use.	
5	 A protected enzyme system for use in a liquid cleaning composition, said system comprising at least one detergent enzyme dispersed is a hydrophobic substance, which is substantially insoluble in the liquid cleaning composition but dispersible therein as particles or droplets, and which is sufficiently fluid or friable to be disrupted under cleaning conditions. A system according to claim 2, comprising a hydrophilic solution of at least one detergent enzyme dispersed in a hydrophobic liquid. 	5
10	 4. A system according to claim 2 comprising particles of a solid composition which contain at least one detergent enzyme and which are dispersed in a hydrophobic liquid. 5. A protected enzyme system for use in a liquid cleaning composition consisting essentially of granules comprising at least one detergent enzyme encapsulated within a hydrophobic substance which is not substantially soluble in the liquid cleaning composition and which is fluid or 	10
15	hydrophobic substance which is substantially insoluble as herein defined in aqueous based liquid laundry detergents and which has a softening point below 60°C.	15
20	7. A protected enzyme system for use in aqueous based liquid detergents, said system comprising at least one detergent enzyme dispersed in a hydrophobic substance which is substantially insoluble in said liquid detergents and which has a melting point below 60°C. 8. A protected enzyme system according to claim 7 wherein said hydrophobic substance has a melting point below 50°C.	20
05	9. A system according to claim 8 wherein said hydrophobic substance has a melting point below 40°C.	25
25	hydrophobic liquid which is substantially insoluble in aqueous based liquid laundry detergents. 11. A system according to any foregoing claim wherein the hydrophobic substance has a viscosity greater than 0.8 Pascal seconds at 24 sec. 1 shear and 25°C.	
30	12. A system according to claim 11, wherein the hydrophobic substance has a viscosity greater than 10 Pascal seconds at 24 sec 1 shear and 25°C. 13. A system according to any foregoing claim wherein the hydrophobic substance has a	30
35	viscosity less than 200 Pascal seconds at 24 sec ¹ shear and 60°C. 14. A system according to claim 13, wherein the hydrophobic substance has a viscosity less than 60 Pascal seconds at 24 sec ¹ shear and 60°C. 15. A system according to claim 14, wherein the hydrophobic substance has a viscosity between 1 and 50 Pascal seconds at ambient temperature.	35
40	16. A system according to any foregoing claim having a viscosity greater than 2 Pascal seconds at 24 sec ¹ shear and 25°C. 17. A system according to claim 16 having a viscosity greater than 10 Pascal seconds at 24 sec ¹ shear and 25°C. 18. A system according to any foregoing claim having a viscosity less than 200 Pascal seconds at 24 sec ¹ shear and 60°C.	40
45	19. A system according to any of claims 16 to 18 having a viscosity of from 2 to 60 Pascal seconds at 24 sec ¹ shear and 25°C.	45
50	organosiloxane polymer.	50
55	hydrophobic phosphate ester.	55
60	27. A system according to any foregoing claim, wherein said enzyme comprises one or more of a protease, a lipase an amylase and a cellulase. 28. A method of protecting an enzyme for storage, prior to use, as a discontinuous phase dispersed in an environment which tends to degrade unprotected enzymes, which comprises dispersing the enzyme in a hydrophobic material which is insoluble in the said environment, and which is a liquid under the normal conditions of use and dispersing said hydrophobic material in	60
65	said environment. 29. A method for protecting at least one detergent enzyme for use in a liquid detergent composition which comprises dispersing said enzyme in a hydrophobic material which is sub-	65

	stantially insoluble in said liquid detergent but which is dispersible therein as particles or droplets, and which is liquid under normal washing conditions.	
	30. A liquid cleaning composition having dispersed therein particles or droplets of a protected	
5	enzyme system according to any of claims 1 to 27. 31. A composition according to claim 30 comprising surfactant and water. 32. A liquid cleaning composition according to claim 31 comprising water, a surfactant, sufficient electrolyte dissolved in the composition to form with the surfactant a structure capable	5
	of supporting dispersed solid or liquid particles or droplets, and a protected enzyme system according to any of claims 1 to 27, dispersed in the composition.	
10	33. A composition according to claim 32 which contains a builder. 34. A composition according to claim 33 wherein said builder is at least partially present as	10
	suspended solid particles.	
	35. A composition according to any of claims 30 to 34 having an alkaline pH. 36. A composition according to claim 35 having a pH of from 7.5 to 12.	
15	37. A composition according to claim 36 having a pH of from 8 to 11.	15
	38. A composition according to any of claims 30 to 37 wherein the surfactant comprises an	
	anionic and/or a nonionic surfactant. 39. A composition according to claim 38, comprising (i) an alkyl benzene sulphonate, and (ii)	
	an alkyl ether sulphate and/or a nonionic surfactant.	
20	40. A composition according to any of claims 33 to 39, wherein the builder comprises a	20
	condensed phosphate, an orthophosphate, a phosphonate, a zeolite, an alkali metal carbonate, an alkali metal silicate, a nitrilotriacetate, a citrate and/or an ethylenediamine tetracetate.	
	41. A composition according to claim 40, wherein the builder comprises sodium tripolyphos-	
	phate.	0.5
25	42. A composition according to any of claims 31 to 41, wherein the electrolyte comprises a dissolved portion of the builder and/or an added water-soluble non-surface active salt which	25
	tends to salt surfactant out of solution.	
	43. A composition according to any of claims 30 to 42, comprising from 5 to 30% by	
-	weight of surfactant and from 0.01 to 10% by weight of the protected enzyme system. 44. A composition according to any of claims 33 to 43, containing from 10 to 40% by	30
30	weight of builder.	30
	45. A composition according to any of claims 30 to 44 which additionally contains at least	
35	one of a soil suspending agent, an optical brightener, perfume, a bleach and a colourant. 46. A composition according to claim 45 containing sodium carboxymethyl cellulose. 47. A powder cleaning composition containing a protected enzyme system according to any	35
	of claims 1 to 4 and 6 to 27.	
	48. A detergent powder according to claim 47 containing at least one surfactant, a builder and a solid filler.	
	49. A detergent powder according to claim 48 containing a bleach.	
40	50. A detergent powder according to any of claims 47 to 49 wherein the surfactant comprises sodium alkyl benzene sulphonate and at least one of an alkylether sulphate and a non-ionic surfactant.	40
	51. A composition according to any of claims 48 to 50 wherein the builder comprises	
	sodium tripolyphosphate.	45"
45	52. A composition according to any of claims 48 to 51 wherein the filler is sodium sulphate.53. A composition according to any of claims 49 to 52 wherein the bleach is sodium	45
	perborate.	
	54. A mechanical dishwashing powder containing a protected enzyme system according to	
50	any of claims 1 to 27. 55. A dishwashing powder according to claim 54 containing from 30 to 60% of alkali.	50
50	56. A dishwashing powder according to claim 55 wherein said alkali comprises sodium	
	carbonate.	
	57. A dishwashing powder according to any of claims 54 to 56 containing from 10 to 40% by weight of sodium tripolyphosphate.	
55		55
•	non-ionic surfactant.	
	59. A dishwashing powder according to any of claims 54 to 58 containing a silicate. 60. A hard surface cleaner containing a protected enzyme system according to any of claims	
60	1 to 27. 61. A hard surface cleaner according to claim 60 which comprises from 1 to 10% by weight	60
50	of anionic and/or non-ionic surfactant, from 2 to 15% by weight of dissolved builder and from 1	
•	to 10% by weight of hydrotrope.	
	62. A hard surface cleaner according to claim 61 wherein said builder is potassium pyrophosphate.	
65	and the second control of the second control	.65

	an alkali metal benzene or alkyl benzene, sulphonate having up to 4 aliphatic carbon atoms. 64. A scouring cream according to any of claims 60 to 63. 65. A scouring cream according to claim 64 containing up to 70% by weight of an abrasive	
5	suspended therein. 66. A scouring cream according to claim 65 wherein said abrasive is silica or calcium	5
	67. An oven cleaner containing a protected enzyme system according to any of claims 1 to	
10	68. An oven cleaner according to claim 67 containing from 2 to 15% by weight of sodium or potassium hydroxide and from 2 to 15% by weight of anionic and/or non-ionic surfactant.	10
	ionic and/or anionic surfactant, from 5 to 40% by weight of a water-miscible liquid lower mono-, di- or poly-hydric alcohol or ether alcohol, and from 5 to 15% by weight of a builder. 70. A carpet shampoo containing a protected enzyme system according to any of claims 1	15
15	to 27. 71. A carpet shampoo according to claim 70 comprising from 2 to 20% by weight of anionic and/or non-ionic surfactants.	15
	72. A carpet shampoo according to claim 71 wherein said surfactant is a mixture of an alkyl	
20		20
	scribed herein with reference to any of the examples. 75. A composition according to any of claims 30 to 47 substantially as described herein with	25
25	reference to any of the examples. 76. A composition consisting essentially of a detergent enzyme dispersed in a hydrophobic fluid which has a viscosity of from 0.05 to 200 Pascal seconds.	
	77. A composition according to any of claims 1 to 27 and 76 wherein said hydrophobic lidid	
30	78. A composition according to claim 77 wherein said hydrophobic fluid has a viscosity of	30
	79. A composition according to claim 78 wherein said hydrophobic fluid has a viscosity of from 2 to 50 Pascal seconds.	

Printed for Her Majesty's Stationery Office by Burgess & Son (Abragdon) Ltd, Dd 8991685, 1987.
Published at The Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.

THE PACE BLANT DE PROPERTO